



Extra length
valances

Image Not Yet Available



Hood fitting
service available

PACKAWAY HOOD MIDGET 1961-64 (NO ZIP OUT WINDOW)

Black double duck hood, fitting the grey two piece 'packaway' hood frame used on 948cc and 1098cc Midgets and Sprites between 1961 and 1964 (sidescreen models, not wind up window models). Double duck is two layers of automotive grade canvas, weatherproofed by a rubberised layer sandwiched in between, providing an affordable upmarket natural fabric appearance.

All Club hoods feature padded and strengthened extra length valances for improved weathersealing and durability. Every possible fastener is factory fitted and the hood retaining strip sleeves are jig-located to keep necessary adjustments during fitting to a minimum.

Before fitting a new hood to a 1961-64 Midget or Sprite, ensure that the spring loading is strong and locking mechanisms on each half of the hood frame are working freely - this will be crucial in getting a consistently taut hood. Hoods on later cars are tensioned by clamping the header rail to the windscreen, whereas hoods on these cars are tensioned by the spring loading of the frame.



Easy to fit. Fitting a new Midget packaway hood is not the difficult task often rumoured. Because there is no header rail on this type of hood, adjustments are kept to a minimum and the hood can be fitted in around 1 1/2 to 2 hours.

FITTING INSTRUCTIONS



Basic hand tools required. Craft knife or hole punch, tape measure and chalk, pliers (for fitting turnbuckles etc.). Additionally, screwing together the two halves of a 'Tenax' pull-button fastener can be adequately achieved with a bradawl or similar pointed tool but is far easier with a Tenax key.

MORE GREAT RECOMMENDATIONS:



FABSIL WATER REPELLANT



RENOVO PLASTIC
REAR SCREEN POLISH



RENOVO HOOD SHAMPOO
(300ml)