

ELECTRIC WASHER KIT (F325/F325Q)

Application: MGB/C/GT/V8

Contents: 1 X washer pump, 1 X switch
1m Wire, 1m washer tubing
2 X Self tapping screws
5 X Spade connectors
1 X Ring terminal

Instructions

1. Find a convenient place in the engine bay to mount the pump, near to the washer tube.
2. With care drill two pilot holes for the self-tapping screws and then mount the pump, making sure that the outlets are to the bottom of the unit. Fasten with one screw only at this point.
3. With the wire supplied attach one spade connector to it and slide it on to the negative terminal of the pump.
4. Cut the wire to length and attach the ring terminal to the second pump mounting screw and screw it in. Remove the old washer pump control from the dashboard and attach the new pump switch in its place.
5. A wire can now be run from the pump up to a terminal on the switch. Run a wire from the other terminal on the switch to a live supply, such as the ignition switch or fuse box. Make sure that the supply turns on and off with the ignition ie not live all the time.
6. Cut the washer tube near to the pump and attach the tube from the washer bottle to the inlet side of the pump. Note the direction indicator arrow on the pump.
7. Now connect the tube supplied to the other outlet of the pump and take it round the engine bay through the bulkhead and up to the washer jet (if single only fitted) or to a T piece if two jets are fitted.
8. Now check that there is water in the washer bottle, switch on the ignition and try the washers.
9. If you have any queries on fitting this item please ring the MGOC Spares & Accessories department on 01954 231318 we will be pleased to help with your enquiry.